

INSTALLATION INSTRUCTIONS

LCD Wall Mount

The EasyMount LCD Wall Mount allows you to easily and securely hang your LCD Monitor on any wall within your home. We greatly appreciate your purchase of the EasyMount LCD Wall Mount. Please read these instructions carefully to ensure proper use.

Mounting Equipment Included



Monitor Plate

Wall Plate

(2) 2.5 " Dry Wall Screws

(4) LCD Mount Screws

CAUTION

Installer must make sure that LCD Wall Mount is positively and securely attached and that fasteners appropriate to material are used.

Before Installing, check to make sure all parts of the mount are included.

Make sure all screws and bolts are tightened before allowing Wall Mount to bear the full weight of the LCD Display.

Assembly/Installation

① Attaching EasyMount to the back of your LCD monitor: Place the 4 Mount Screws into the holes (VESA compliant) on the Monitor Plate and tighten them snugly to the back of the LCD monitor (Figure 1). **Note:** Only tighten Mount Screws until they are secure, do not over tighten.



Figure 1

② Find a proper place to fasten to the wall: Using a high quality Stud Finder (Not Included) to locate a stud (Figure 2). It is recommended to use a awl or nail to verify the stud location and create an initial beginning point for mounting.




Figure 2

③ Attaching EasyMount to wall: Once you have the location for the wall mount, take the Wall Plate and screw in the top screw ONLY (Figure 3). Using the built-in level, adjust the Wall Plate until it is straight (Figure 4). When Wall Plate is level, screw in the bottom screw to complete its secure fastening to the wall.



Figure 3



Figure 4

④ Attaching LCD monitor to wall: Slide the Monitor Plate overtop of the Wall Plate until it locks into place (Figure 5). The Easy Mount cord management system keeps cords from dangling and becoming tangled (Part A Figure 6). Use the Posi-Lock Lever to adjust the LCD Wall Mount (Part B Figure 6).



Figure 5




Figure 6